

H Series LY938

AI识图



H系列LY938 详细参数/H Series LY938 Detailed Specifications

柴油发动机/Diesel engine	新长柴4102涡轮增压/XinChangchai 4102 Turbocharged Diesel Engine
额定功率/Rated power	18 kW
额定载荷/Rated Load	1800kg
铲斗宽度/Bucket width	1.9m
额定铲斗容量/Rated bucket capacity	0.9m ³
轮距/Wheel base	2.26m
轮胎型号/Tire model	20.5-16 人字胎/20.5-16 herringbone tire
卸货高度/Dumping height	3.2m
平举高度/Flat lift height	3.8m
卸货距离/Unloading distance	1m
最小转弯半径/minimum turning radius	3.2m
驾驶方式/Driving method	四轮驱动/Four-wheel drive
驱动桥型号/Drive axle model	轮边减速桥/Wheel-end reduction axle
液压泵模式/Hydraulic pump mode	40
液压系统最大压力/Maximum hydraulic system pressure	20Mpa
最大行走速度/Maximum walking speed	35公里/小时/35 kilometers per hour
传动系统/Transmission system	无级变速双高速和低速 /Continuously variable speed dual high and low speed
冷却系统/Cooling System	双片式液压变矩器油散热器 /Dual piece hydraulic torque converter oil radiator
整车重量/Overall weight	3.3T
车辆尺寸/vehicle size	5.5m*1.8m*2.75m